

- Drum fan series with high air volume.
- Ideal for use in production, warehouse and logistic areas.
- 3 speeds selectable by push button switch.
- Two-pole on/off switch.
- Vertical grade in 360° range adjustable.
- Housing, blades, protective grillle and tubular steel frame matt black finish.
- Wall mounting possible using accessory WHDF #96080.
- Stable, tilt-free tubular steel frame with transport wheels and rubber feet.
- Useful transport handles at the housing and cable coil at the back side of protective grille.
- High-performance Aluminum blade.
- Protection class IP54 dust and splash-proof.
- Rubber sheathed cable H07RN-F G 3 1.0 mm², length 2.5 m with protective contact plug IP54.












Wall mounting accessory
WHDF # 96080 please order separately





Dimensions mm



С	
<u>-</u>	D

Model DF ECO	800	600
Grille Ø (mm)	800	650
Blade Ø (mm)	750	600
Dim. A/B	880/83	30 750/680
Dim. C/D	260/92	20 270/770
Power motor (W)	123	123
Voltage (V/Hz)	220-2	240/50
No. of speeds	3	}
Rev. (RPM)	870	870
Weight (kg)	19.3	16.3

## DF600/800 Eco IP54 SL

Product	Code No.	Housing/Grille Finish	Blade Finish
DF800 ECO IP54 SL	308095	Matt black	Black
DF600 ECO IP54 SL	306090	Matt black	Black